



AORALSCAN 3 WIRELESS

Intraoral Scanner

Scan Without Limits

SHINING 3D
DENTAL





Go Wireless

Provides a more comfortable experience for dentist and patient without restraints from a wired setup.



Fast and Stable

Built-in Wi-Fi 6 technology enables a seamless scan experience with fast and stable data transmission.



Long-lasting Battery Life

Up to 2 hours of continuous scanning for each charge, with 3 batteries included. Enjoy smooth scanning and a seamless workflow with a long battery life.



Next-level Software Functions

Faster data post-processing speed. Self-developed clinic-friendly functions, including Orthodontic Simulation, Model Creator, Temp Design, Indirect Bonding Tray Design, Oral Health Report and Data Track.

2
hours

2 hours of continuous scanning.

10
days

10 days under standby mode.

2
min


one case scanning time: 2 min*

(maxillary+ mandibular+occlusion)


*performance may vary according to different situation.

60
cases

1 charge can be utilized for up to 60 cases



Standard tip



Mini tip

Scan Field	Standard scanner tip: 16 mm × 12 mm × 22 mm Mini scanner tip: 12 mm × 9 mm × 22 mm
Scan Depth	-2mm to 20 mm from exit surface of tip
Scan Tip Sterilization	Autoclavable up to 100 times 121°C 102.9kPa 30 mins 134°C 205.8kPa 4 mins
Scan Tip Heating	40s instant heating(Anti-fogging)
Scan Principle	Non-contact scanning with the structured light
Wireless Technology	Wi-Fi 6(802.11a/n/ac/ax)
Effective Wireless Range	Same room, up to 5m
Battery Life	2 hours of continuous scanning. 10 days standby mode
Dimension (L * W * H)	270(L)x50(W)x40(H)mm(includes battery, tip)
Total Weight	330g±20(includes battery, tip)
Output	STL, OBJ, PLY
Connector	USB 3.0
Power Input	12V DC/3A